

Serenity

Tuft gauge	1/8 cut pile	ISO 2424
Pilecomposition	100% PP	ISO 2424
Primary Backing	Woven	ISO 2424
Secondary backing	Felt	ISO 2424
Width	400 cm, 500 cm	± 1% EN 984
Pile Weight	1420 gr/m ²	ISO 8543
Total weight	Felt : 2220 gr/m ²	± 15% ISO 8543
Pile height	10.5 mm	± 2 mm ISO 1766
Total Height	Felt : 13.5 mm	ISO 1765
Number of knots	145.360 /m ²	-7.5% .+10% ISO 1763
Fire Classification	Efl	EN 13501-1
Use Area	Heavy domestic use (23)	EN 1307
Light fastness	≥ 5	105-B02
Wearebility	≥ 4	105-X12
Water fastness	≥ 4	105-E01

Floorsymbols



Certificates

 2024 Condor Carpets Euroweg 3 8061 SB Hasselt EN1307 DOP: C-001FS339 Reaction to fire: Efl Slip resistance: DS Felt Resilient floor covering to be used within a building	 2024 Condor Carpets Euroweg 3 8061 SB Hasselt EN1307 DOP: C-001FS339-UK Reaction to fire: Efl Slip resistance: DS Felt Resilient floor covering to be used within a building	 www.blauer-engel.de/uz128			
---	--	--	---	---	---