

# nevada divine

38MM



WARRANTY



CERTIFIED



UV STABLE



CHLORE  
RESISTANT



MiNT



MADE  
IN EUROPE

|                                                                                                           |                                      |
|-----------------------------------------------------------------------------------------------------------|--------------------------------------|
| PILE HEIGHT / POLHÖHE / HAUTEUR DE LA FIBRE / ALTURA DE PELO                                              | ± 38 MM                              |
| # STITCHES / STICHZAHL / NÆUDS / PUNTADAS                                                                 | ± 23 ST / 10 CM                      |
| # TUFTS / NOPPENZAHL / TOUFFES / MECHONES                                                                 | ± 24150 / M²                         |
| GAUGE / TEILUNG / JAUGE / CALIBRE                                                                         | 3/8"                                 |
| LINEAR DENSITY / LINEARE DICHTÉ / DENSITÉ LINÉAIRE / DENSIDAD LINEAL                                      | ± 10600 DTEX                         |
| PILE WEIGHT / POLGEWICHT / POIDS DE LA FIBRE / PESO DEL PELO                                              | ± 2227 G / M²                        |
| TOTAL WEIGHT / GESAMTGEWICHT / POIDS TOTAL / PESO TOTAL                                                   | ± 3197 G / M²                        |
| FIBRE SHAPE / FASERFORM / FORME DE FIBRE / FORMA DE FIBRA                                                 | MiNT (MICRO NERVE TECHNOLOGY)        |
| FIBRE / FASER / FIBRE / FIBRA                                                                             | 65 % PE / 35 % PP STRAIGHT + CURLED  |
| BACKING / RÜCKEN / DOSSIER SECONDAIRE / REVERSO                                                           | PRE COAT, ± 800 G / M²               |
| PRODUCTION / PRODUKTION / FABRICATION / PRODUCCIÓN                                                        | TUFTING                              |
| TUFT CLOTH / TUFTTUCH / DOSSIER PRIMAIRE /<br>TEJIDO DE LA ALFOMBRA                                       | POLYPROPYLENE WOVEN, ± 170 G / M²    |
| ROLL WIDTH / ROLLBREITE / LARGEUR DES ROULEAUX / ANCHO DEL ROLLO                                          | ± 2 & 4 & 5 M                        |
| ROLL LENGTH / ROLLENLÄNGE / LONGUEUR DES ROULEAUX / LONGITUD DEL ROLLO                                    | ± 25 M                               |
| UV STABILITY / UV STABILITÄT / STABILITÉ À LA RADIATION UV / ESTABILIDAD UV                               | > 3000 HOURS UV-A / 6000 HOURS XENON |
| LIGHT FASTNESS / FARBECHTHEIT / TENUE DES COULEURS / SOLIDEZ A LA LUZ                                     | SCALE 7 (DIN 54004)                  |
| CHLORE RESISTANCE / CHLORRESISTENT / RÉSISTANCE AU CHLORE /<br>RESISTENCIA AL CLORO                       | SCALE 4 – 5 (DIN 54019)              |
| RESISTANCE TO SEA WATER / SALZWASSERRESISTENT /<br>RÉSISTANCE À L'EAU DE MER / RESISTENCIA AL AGUA SALADA | SCALE 4 – 5 (DIN 54007)              |
| WATER PERMEABILITY / WASSERDURCHLÄSSIGKEIT / PERMÉABILITÉ À L'EAU /<br>PERMEABILIDAD AL AGUA              | ± 60 LITER / M² PER MINUTE           |
| YEARS OF WARRANTY / JAHRE GARANTIE / ANNÉES DE GARANTIE / AÑOS DE GARANTÍA                                | 10 YEARS                             |

Domo® Landscaping is a brand of Sports and Leisure Group nv. The company reserves the right to amend the technical specifications of this product without prior notice. Sports and Leisure Group nv guarantees the technical quality of the product. While we strive to ensure the accuracy of the listed product specifications, minor deviations in delivered products may occur due to ongoing improvements or other factors.

Industriepark-West 43  
9100 Sint-Niklaas  
Belgium

T: +32 (0)3 780 45 75  
orders@domolandscaping.com  
www.domolandscaping.com

